



Ocular Lensmeter


- Adjustment of the body angle
- Easy to handle
- Bright and clear visible measuring mark
- Internal reading
- Including prism compensator
- Marking system: with ink pad

Standard equipment:

- 1 ink pad, 1x box of ink, 1 dust cover

2355 20

 12 month warranty!

 For **spare parts** contact your local distributor.



Accessories for Ocular Lensmeter

Ink for Ocular Lensmeter

2355 19

Technical Data for all Devices at a Glance

| Technical data | 2357 10 BS-4000 WF | 2355 20 Ocular |
|--|------------------------------------|---|
| Measuring range | | |
| Sphere: | - 25 to + 25 dpt. | - 25 to + 25 dpt. |
| Cylinder: | - 10 to + 10 dpt. | - 25 to + 25 dpt. |
| Axis: | 0° to 180° | 0° to 180° |
| Addition: | 0 to 10 dpt. | all in the measuring range |
| Prism: | 0 to 15 Δ | 0 to 20 Δ |
| Measuring units | | |
| Diopters: | 0.01/0.12/0.25 dpt. | 0.125 dpt. to ± 5.0 dpt. 0.25 dpt. to ± 5.0 dpt. |
| Prism: | 0.01/0.12/0.25 Δ | 0.5 dpt. to ± 2.0 dpt. 1.0 dpt. to ± 2.0 dpt. |
| Prism display: | Cartesian and polar coordinates | Polar coordinates |
| Measurements | | |
| Optical measuring light Ø 8 mm: | X | |
| Pupil distance 50 to 86 mm (steps 0.5 mm): | X | |
| UV transmission 0 to 100 % (375 nm): | X | |
| Measures standard lenses: | X | X |
| Measures bifocals: | X | X |
| Measures trifocals: | X | X |
| Measures progressive lenses: | X | |
| Measures contact lenses: | X | |
| Monitor display | | |
| Colour touch-screen: | X | |
| External communication | | |
| Serial interface RS-232C: | X | |
| General | | |
| Thermal printer: | X | |
| Power: | 25 W | 35 W |
| Power usage per 10 min: | 0.0042 kWh | 0.0058 kWh |
| Voltage: | 240 V | 240 V |
| Size (w x h x d): | 161 x 372 x 222 mm | 150 x 450 x 280 mm |
| Weight: | 5.5 kg | 4.9 kg |